





Declaration of performance Number 144 Nelissen facing bricks											
(1) Unique identification code of the product-type: MAGNOLIA	(6) System or systems of assessment and verification of constancy of performance of the construction product: 2+	(4) Manufacturer Nelissen facing bricks Kiezelweg 460 B-3620 Lanaken Tel: +32 (0)12 44 02 44 Fax: +32 (0)12 45 53 89		NB 0749 EN 771-1 2011 +A1:2015				 06 			
(2) Type number: 3	(7) Notified body: Notified Body BCCA N° NB 0749 performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.	www.nelissen.be									
(3) Intended use or uses of the construction product: Units for use in unprotected masonry walls, columns and partitions.	(9) Declared performance: <i>For available sizes refer to the product sheet and / or website.</i>										
Dimensions	M50	M65	RF	WV50	WV65	N70/4	N70/5	NNF	Dubio		
Length (mm)	190	190	210	210	215	240	240	243	240		
Width (mm)	90	90	100	100	102	72	72	109	72		
Height (mm)	51	64	40	49	65	40	50	73	70		
Normalised compressive strength. (N/mm ²)	Cat. I , <input type="checkbox"/>		22	25	22	22	25	15	24	26	26
Mean compressive strength (N/mm ²)			30	30	30	30	30	20	30	30	30
Tolerance category	T2										
Range category	R1										
Net dry density	NPD						Kg/mm ³				
Configuration	1										
Water vapour permeability	5/10										
Durability against freeze thaw	F2										
Dimensional stability: moisture expansion	NPD						Mm/m				
Reaction to fire	A1										
Flatness of bed faces	NPD										
Plane parallelism of bed faces	NPD										
Gross dry density	1400(D2)						Kg/mm ³				
Bond strength	NPD						N/mm ²				
Thermal conductivity (λ10,dry,mat(90,90))	0,49 (S2)						W/mK				
Thermal conductivity (λ10,dry,mat) EN1745 Annex A	0,45 (S1)						W/mK				
Water absorption	16						%				
Initial water absorption	1,5<IW<=4 (IW klasse 3)						Kg/(m ² .min)				
Active soluble salts	S2										
Dangerous substances	NPD										
(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:											
Signed for and on behalf of the manufacturer by:											
Burt Nelissen (General Management)											
											
Lanaken (B) 19.02.2020											