

Declaration of performance



umber NEHVB009_2_EN_21084											CE	
Product type / CE	MANGANESE BLACK									06		
Intended use or uses of the construction product	Units for use in unprotected masonry walls, colums and p						partition	IS.		1		
Manufacturer							2 (0)12 44 02 44 2 (0)12 45 53 89 lissen.be					
System or systems of assessment and verification of constancy of performance of the construction product	2+											
Notified body	BCCA NB 0749											
Harmonized standard	EN 771-1:2011 +A1:20											
Notified Body performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.												
Declared performance			Fo	or availa	able size	s refer t	to the p	roduct s	heet ar	nd / or w	ebsite.	
Dimensions				M65	N70/4	N70/5	N70/7	NNF	RF	WV50	WV65	
Length (mm)				188	239	239	240	241	208	209	213	
Width (mm)				88	72	72	70	108	100	100	101	
Height	(mm)	51	64	40	50	70	73	40	49	65		
Compressive strength.	(N/mm²)	Cat. I , 🗆	22	25	15	24	26	26	22	22	25	
Mean compressive strength	(N/mm²)		30	30	20	30	30	30	30	30	30	
Tolerance category								T2				
Range category								R1				
Flatness of bed faces								NPD				
Plane parallelism of bed faces								NPD				
Gross dry density							1630(D1)			Kg/m³		
Net dry density							NPD			Kg/m³		
Configuration								1				
Bond strength								NPD	N/mm²			
Thermal conductivity (λ10,dry,mat(90,90))								0,59 (S2)			W/mK	
Thermal conductivity (λ10,dry,mat) EN1745 Annex A							0,55 (S1)			W/mK		
Water vapour permeability							5/10					
Freeze/Thaw resistance							F2					
Water absorption							14			%		
Initial water absorption							1,5 <iw<=4< td=""><td colspan="2">Kg/(m².min)</td></iw<=4<>			Kg/(m².min)		
Active soluble salts							S2					
Dimensional stability: moisture expansion							NPD			Mm/m		
Reaction to fire							A1					
Dangerous substances							NPD					
The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above.												

Signed for and on behalf of the manufacturer by

Burt Nelissen (General Management)

Lanaken (B) 25.03.2021