



Declaration of performance

Number	NEHVB015_2_EN_21084	$C \in$				
Product type / CE	T15		06			
Intended use or uses of the construction product	Units for use in unprotected masonry walls, colums and partitions.					
Manufacturer	Nelissen Steenfabrieken NV Kiezelweg 460 B-3620 Lanaken	Tel: +32 (0)12 44 02 44 Fax: +32 (0)12 45 53 89 info@nelissen.be				
System or systems of assessment and verification of constancy of performance of the construction product	2+					
Notified body	BCCA NB 0749					
Harmonized standard	EN 771-1:2011 +A1:2015					

Notified Body performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.

Declared performance

For available sizes refer to the product sheet and / or website.

•							,			,	
Dimensions			M50	M65	N70/4	N70/5	N70/7	NNF	RF	WV50	WV65
Length (mm)			190	190	240	240	240	243	210	210	215
Width		(mm)	90	90	72	72	72	109	100	100	102
Height		(mm)	51	64	40	50	70	73	40	49	65
Compressive strength.	(N/mm²)	Cat. I , □	22	25	15	24	26	26	22	22	25
Mean compressive strength	(N/mm²)		30	30	20	30	30	30	30	30	30
Tolerance category								T2			
Range category								R1			
Flatness of bed faces	atness of bed faces								NPD		
Plane parallelism of bed faces								NPD			
Gross dry density								1500(D1)			
Net dry density									NPD		
Configuration								1			
Bond strength							NPD			N/mm²	
Thermal conductivity		(λ10,dry,mat(90,90))						0,49 (S2)			
Thermal conductivity		(λ10,dry,mat) EN1745 Annex A						0,45 (S1)			
Water vapour permeability								5/10			
Freeze/Thaw resistance								F2			
Water absorption							16			%	
Initial water absorption							1,5 <iw<=4< td=""><td>Kg/(m².r</td><td>min)</td></iw<=4<>			Kg/(m².r	min)
Active soluble salts								S2			
Dimensional stability: moisture expansion								NPD		Mm/m	
Reaction to fire								A1			
Dangerous substances								NPD			

The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above.

Signed for and on behalf of the manufacturer by

Burt Nelissen (General Management)

Lanaken (B)

25.03.2021