

Declaration of performance



Num	ber	NEHVB035_2_EN_21084									(6	
Product type / CE		TRAFALGAR									Ō	6	
Intended use or uses of the construction product		Units for use in unprotected masonry walls, colums and partitions.											
Manufacturer		Nelissen Steenfabrieken NVTel: +32 (Kiezelweg 460Fax: +32B-3620 Lanakeninfo@nelis							45 53 8				
System or systems of assessment and verification of constancy of performance of the construction product		2+											
Notif	ied body	BCCA NB 0749											
Harn	nonized standard	EN 771-1:2011 +A1:2015											
	ied Body performed under system 2+ the initial ins nuous surveillance, assessment and evaluation of t rol.											uction	
Decla	ared performance	For available sizes refer to the product shee								heet ar	d / or v	ebsite.	
D	imensions			M50	M65	N70/4	N70/5	N70/7	NNF	RF	WV50	WV65	
Le	ength		(mm)	188	188	239	239	240	241	208	209	213	
W	/idth		(mm)	88	88	72	72	70	108	100	100	101	
н	eight		(mm)	51	64	40	50	70	73	40	49	65	
C	ompressive strength.	(N/mm²)	Cat. I , ⊥	22	25	15	24	26	26	22	22	25	
М	ean compressive strength	(N/mm²)	outini,	30	30	20	30	30	30	30	30	30	
Т	Tolerance category								Т2				
R	Range category Flatness of bed faces								R1				
Fl									NPD				
PI	Plane parallelism of bed faces								NPD				
G	Gross dry density								1630(D1)	Kg/m³			
N	Net dry density								NPD			Kg/m³	
Configuration									1				
В	Bond strength								NPD	N/mm²			
Т	Thermal conductivity (λ10,dry,mat(90,90))								0,59 (S2)	W/mK			
Т	Thermal conductivity (λ10,dry,mat) EN1745 Annex A							0,55 (S1)			W/mK		
W	Water vapour permeability								5/10				
Freeze/Thaw resistance									F2				
Water absorption								14			%		
Initial water absorption								1,5 <iw<=4< td=""><td colspan="2">Kg/(m².min)</td></iw<=4<>			Kg/(m².min)		
Active soluble salts								S 2					
Dimensional stability: moisture expansion								NPD			Mm/m		
Reaction to fire								A1					
D	angerous substances							NPD					
The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above.													
Cian	ad for and on bobalf of the manufacturor by						D.	urt Molice		n a una l M	_		

Signed for and on behalf of the manufacturer by

Burt Nelissen (General Management)

Lanaken (B) 25.03.2021