

## Declaration of performance



| Nu  | Imber   | NEHVB041B_2_EN_21084   |                     |     |     |       |       |   |   |        | (6          |       |  |
|---|---|--|---------------------|-----|-----|-------|-------|---|---|--------|-------------|-------|--|
| Pro   | oduct type / CE   | OLD-GOTHIC BAEKEL  |                     |     |     |       |       |   |   |        |             |       |  |
| Int   | tended use or uses of the construction product  | Units for use in unprotected masonry walls, colums and parti |                     |     |     |       |       |   | IS.   |        |             |       |  |
| Ma  | anufacturer   |  |                     |     |     |       |       |   | (0)12 44 02 44<br>(0)12 45 53 89<br>ssen.be |        |             |       |  |
|   | stem or systems of assessment and verification of nstancy of performance of the construction product  | 2+   |                     |     |     |       |       |   |   |        |             |       |  |
| Nc  | tified body   | BCCA NB 0749   |                     |     |     |       |       |   |   |        |             |       |  |
| На  | rmonized standard   | EN 771-1:2011 +A1:2015                                       |                     |     |     |       |       |   |   |        |             |       |  |
| Notified Body performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control. |   |  |                     |     |     |       |       |   |   | uction |             |       |  |
| De  | clared performance  | For available sizes refer t                                  |                     |     |     |       |       |   | to the product sheet and / or website.      |        |             |       |  |
|   | Dimensions  |  |                     | M50 | M65 | N70/4 | N70/5 | N70/7   | NNF   | RF     | WV50        | WV65  |  |
|   | Length (mr  |  |                     |     | 188 | 239   | 239   | 240   | 241   | 208    | 209         | 213   |  |
|   | Width (mr   |  |                     |     | 88  | 72    | 72    | 70  | 108   | 100    | 100         | 101   |  |
|   | Height (mn  |  |                     |     | 64  | 40    | 50    | 70  | 73  | 40     | 49          | 65    |  |
|   | Compressive strength.   | (N/mm²)  | Cat. I , $^{\perp}$ | 22  | 25  | 15    | 24    | 26  | 26  | 22     | 22          | 25    |  |
|   | Mean compressive strength   | Cal. 1, -  | 30                  | 30  | 20  | 30    | 30    | 30  | 30  | 30     | 30          |       |  |
|   | Tolerance category  |  |                     |     |     |       |       |   | T2  |        |             |       |  |
|   | Range category  |  |                     |     |     |       |       |   |   | R1     |             |       |  |
|   | latness of bed faces  |  |                     |     |     |       |       |   | NPD   |        |             |       |  |
|   | Plane parallelism of bed faces NPD  |  |                     |     |     |       |       |   |   |        |             |       |  |
|   | Gross dry density   |  |                     |     |     |       |       |   | 1630(D1)                                    |        |             | Kg/m³ |  |
|   | Net dry density   |  |                     |     |     |       |       |   | NPD   |        |             | Kg/m³ |  |
|   | Configuration   |  |                     |     |     |       |       |   |   |        |             |       |  |
|   | Bond strength   |  |                     |     |     |       |       |   | NPD   |        |             | N/mm² |  |
|   | Thermal conductivity (λ10,dry,mat)   Thermal conductivity (λ10,dry,mat) EN1745 Ar   |  |                     |     |     |       |       | 0,59 (S2)   |   |        | W/mK        |       |  |
|   |   |  |                     |     |     |       |       |   | 0,55 (S1)                                   | W/mK   |             |       |  |
|   | Water vapour permeability   Freeze/Thaw resistance  |  |                     |     |     |       |       |   | 5/10  |        |             |       |  |
|   |   |  |                     |     |     |       |       |   | F2  |        |             |       |  |
|   | Water absorption  |  |                     |     |     |       |       |   | 14  |        |             | %     |  |
|   | nitial water absorption   |  |                     |     |     |       |       | 1,5 <iw<=4< td=""><td colspan="2">Kg/(m².min)</td></iw<=4<> |   |        | Kg/(m².min) |       |  |
|   | ctive soluble salts   |  |                     |     |     |       |       |   | S2  |        |             |       |  |
|   | Dimensional stability: moisture expansion   |  |                     |     |     |       |       |   | NPD   | Mm/m   |             |       |  |
|   | Reaction to fire  |  |                     |     |     |       |       | A1  |   |        |             |       |  |
|   | Dangerous substances  |  |                     |     |     |       |       |   | NPD   |        |             |       |  |
|   | The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above. |  |                     |     |     |       |       |   |   |        |             |       |  |

Signed for and on behalf of the manufacturer by

Burt Nelissen (General Management)

Lanaken (B) 25.03.2021