

## Declaration of performance



Number		NEHVB073S050Y 2 EN 21084										6	
Product type / CE		LUNA										ך 1	
Intended use or uses of the construction product		Units for use in unprotected masonry walls, colums and partitions.									-	-	
Manufacturer		Nelissen Steenfabrieken NV Tel: +32 (0							(0)12 44 02 44 (0)12 45 53 89				
System or systems of assessment and verification of constancy of performance of the construction product		2+											
No	tified body	BCCA NB 0749											
Ha	rmonized standard	EN 771-1:2011 +A1:2015											
Notified Body performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory productior control.										uction			
Declared performance		For available sizes refer t							to the product sheet and / or v				
	Dimensions			M50	M65	N70/4	N70/5	N70/7	NNF	RF	WV50	WV65	
	Length		(mm)	188	188	239	239	240	241	208	209	213	
	Width		(mm)	88	88	72	72	70	108	100	100	101	
	Height		(mm)	51	64	40	50	70	73	40	49	65	
	Compressive strength.	(N/mm²)	Cat. I , 🗆	22	25	15	24	26	26	22	22	25	
	Mean compressive strength	30	30	20	30	30	30	30	30	30			
	Tolerance category								Т2				
	Range category							R1					
	Flatness of bed faces Plane parallelism of bed faces Gross dry density								NPD				
									NPD				
									1630(D1)	Kg/m³			
	Net dry density								NPD	Kg/m³			
	Configuration							1					
	Bond strength								NPD	N/mm²			
	Thermal conductivity     (λ10,dry,mat(90,90))								0,59 (S2)	W/mK			
	Thermal conductivity (λ10,dry,mat) EN1745 Annex A								0,55 (S1)	W/mK			
	Water vapour permeability								5/10				
	Freeze/Thaw resistance							F2					
	Water absorption								14	%			
	Initial water absorption								1,5 <iw<=4< td=""><td colspan="2">Kg/(m².min)</td></iw<=4<>			Kg/(m².min)	
	Active soluble salts								S2				
	Dimensional stability: moisture expansion								NPD			Mm/m	
	Reaction to fire								A1				
ŀ	Dangerous substances							NPD					
The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above.													
Signed for and on behalf of the manufacturer by Burt Nelissen (General Management)													

Lanaken (B) 25.03.2021