

Declaration of performance



Number		NEHVB076_2_EN_21084										CE	
Pr	oduct type / CE	MONET										3	
Intended use or uses of the construction product		Units for use in unprotected masonry walls, colums and partitions.											
Manufacturer		Nelissen Steenfabrieken NV Tel: +32 (0)12 44 02 44 Kiezelweg 460 Fax: +32 (0)12 45 53 89 B-3620 Lanaken info@nelissen.be											
	stem or systems of assessment and verification of nstancy of performance of the construction product	2+											
No	ptified body	BCCA NB 0749											
Ha	armonized standard	EN 771-1:2011 +A1:2015											
Notified Body performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory productor control.									uction				
De	eclared performance	For available sizes refer to the proc								roduct sheet and / or website.			
	Dimensions			M50	M65	N70/4	N70/5	N70/7	NNF	RF	WV50	WV65	
	Length		(mm)	192	192	241	241	241	246	212	212	217	
	Width		(mm)	91	91	72	72	72	111	101	101	102	
	Height		(mm)	51	64	40	50	70	73	40	49	65	
	Compressive strength.	(N/mm²)	Cat. I , 🗆	22	25	15	24	26	26	22	22	25	
	Mean compressive strength	(N/mm²)		30	30	20	30	30	30	30	30	30	
	Tolerance category								Т2				
	Range category								R1				
	Flatness of bed faces Plane parallelism of bed faces Gross dry density								NPD				
									NPD				
									1480(D1)	Kg/m³			
	Net dry density								NPD			Kg/m³	
	Configuration								1				
	Bond strength								NPD	N/mm²			
	Thermal conductivity (λ10,dry,mat(90,90)								0,49 (S2)	W/mK			
	Thermal conductivity (λ10,dry,mat) EN1745 Annex								0,45 (S1)	W/mK			
	Water vapour permeability								5/10				
	Freeze/Thaw resistance								F2				
	Water absorption								17	%			
	Initial water absorption							1,5 <iw<=4< td=""><td colspan="2">Kg/(m².min)</td></iw<=4<>			Kg/(m².min)		
	Active soluble salts								S2				
	Dimensional stability: moisture expansion								NPD			Mm/m	
	Reaction to fire								A1				
	Dangerous substances								NPD				
The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above.													

Lanaken (B) 25.03.2021

Signed for and on behalf of the manufacturer by