

Declaration of performance



Number	NEHVB110S050Y_2_EN_21084										6	
Product type / CE	TORBA										τ 1	
Intended use or uses of the construction product	Units for use in unprotected masonry walls, colums and							IS.				
Manufacturer	Nelissen Steenfabrieken NVTel: +32Kiezelweg 460Fax: +32B-3620 Lanakeninfo@neli						2 (0)12 4	45 53 8				
System or systems of assessment and verification of constancy of performance of the construction product	2+											
Notified body	BCCA NB 0749											
Harmonized standard	EN 771-1:2011 +A1:2											
Notified Body performed under system 2+ the initial inscontinuous surveillance, assessment and evaluation of t control.											uction	
Declared performance For available sizes refer t								to the product sheet and / or website.				
Dimensions				M65	N70/4	N70/5	N70/7	NNF	RF	WV50	WV65	
Length (mm)				188	239	239	240	241	208	209	213	
Width (mm)				88	72	72	70	108	100	100	101	
Height	51	64	40	50	70	73	40	49	65			
Compressive strength.	(N/mm²)	Cat. I , 🗆	22	25	15	24	26	26	22	22	25	
Mean compressive strength	out: 1 / 🗆	30	30	20	30	30	30	30	30	30		
Tolerance category								T2				
Range category								R1				
Flatness of bed faces							NPD					
Plane parallelism of bed faces								NPD				
Gross dry density							1630(D1)			Kg/m³		
Net dry density							NPD			Kg/m³		
Configuration								1				
Bond strength								NPD	N/mm²			
Thermal conductivity (λ10,dry,mat(90,90))								0,59 (S2)	W/mK			
Thermal conductivity (λ10,dry,mat) EN1745 Annex A								0,55 (S1)	W/mK			
Water vapour permeability							5/10					
Freeze/Thaw resistance							F2					
Water absorption								14	%			
Initial water absorption							1,5 <iw<=4< td=""><td colspan="2">Kg/(m².min)</td></iw<=4<>			Kg/(m².min)		
Active soluble salts								S 2				
Dimensional stability: moisture expansion							NPD			Mm/m		
Reaction to fire								A1				
Dangerous substances								NPD				
The performance of the product described above is in c accordance with Regulation (EU) no. 305/2011 under t								ormance	e is issu	ed in		
Signed for and on behalf of the manufacturer by Burt Nelissen (General Management)										ent)		

IÇ

Lanaken (B) 25.03.2021