

Declaration of performance



Number		NEHVB113H050W_2_EN_21084										6	
Product type / CE		DIONE 21										1	
Intended use or uses of the construction product		Units for use in unprotected masonry walls, colums and partitions.											
Manufacturer		Nelissen Steenfabrieken NV Tel: +32 (0)12 44 02 44 Kiezelweg 460 Fax: +32 (0)12 45 53 89 B-3620 Lanaken info@nelissen.be											
System or systems of assessment and verification of constancy of performance of the construction product		2+											
Notified body		BCCA NB 0749											
Har	monized standard	EN 771-1:2011 +A1:2015											
Notified Body performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory productor control.									uction				
Dec	lared performance	For available sizes refer							to the product sheet and / or website.				
1	Dimensions			M50	M65	N70/4	N70/5	N70/7	NNF	RF	WV50	WV65	
1	Length		(mm)	188	188	239	239	240	241	208	209	213	
Ľ	Width		(mm)	88	88	72	72	70	108	100	100	101	
	Height		(mm)	51	64	40	50	70	73	40	49	65	
	Compressive strength.	(N/mm²)	Cat. I , ⊥	22	25	15	24	26	26	22	22	25	
1	Mean compressive strength (N/mm ²)					20	30	30	30	30	30	30	
-	olerance category								Т2				
1	Range category Flatness of bed faces Plane parallelism of bed faces Gross dry density								R1				
									NPD				
Γ									NPD				
									1630(D1)	Kg/m³			
	Net dry density								NPD			Kg/m³	
	Configuration								1				
	Bond strength								NPD	N/mm²			
ŀ	Thermal conductivity (λ10,dry,mat(90,90)								0,59 (S2)	W/mK			
ŀ	Thermal conductivity (λ10,dry,mat) EN1745 Annex A								0,55 (S1)	W/mK			
	Water vapour permeability								5/10				
Ī	Freeze/Thaw resistance								F2				
	Water absorption								14	%			
1	Initial water absorption								1,5 <iw<=4< td=""><td colspan="2">Kg/(m².min)</td></iw<=4<>			Kg/(m².min)	
	Active soluble salts								S2				
Ī	Dimensional stability: moisture expansion								NPD			Mm/m	
Ī	Reaction to fire								A1				
Ī	Dangerous substances							NPD					
The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above.													
Siar	ned for and on behalf of the manufacturer by												

a for and on denalt of the manufacturer by

Lanaken (B)

25.03.2021