

**NELISSEN**

Declaration of performance



Number	NEHVB087K050WN_2_GA_24292			
Product type / CE	SARNO			
Intended use or uses of the construction product	Units for use in unprotected masonry walls, columns and partitions.			
Manufacturer	Nelissen Steenfabrieken NV Kiezelweg 460 B-3620 Lanaken		Tel: +32 (0)12 44 02 44 Fax: +32 (0)12 45 53 89 info@nelissen.be	
System or systems of assessment and verification of constancy of performance of the construction product	2+			
	EU	CE	UK	UKCA
Notified body	BCCA NB 0749		BBA N° 0836	
Harmonized standard	EN 771-1:2011 +A1:2015		BS EN 771-1 2011+A1:2015	

Notified Body performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.

Declared performance

Dimensions	MOD 50	MOD 65	N70/4	N70/5	N70/6,5	N70/7	NNF	RF 4	WV 50	WV 65
Length (mm)	190	192	242	241	242	238	244	212	212	217
Width□ (mm)	90	91	72	72	72	72	111	101	101	102
Height (mm)	51	64	41	50	67	70	71	40	51	64
Normalised compressive strength. (N/mm ²)	cat. I, ⊥	22	25	15	24	27	27	27	22	25
Mean compressive strength (N/mm ²)		30	30	20	30	30	30	30	30	30
Tolerance category								T2		
Range category								R1		
Flatness of bed faces								NPD		
Plane parallelism of bed faces								NPD		
Gross dry density								1480(D1)	Kg/m ³	
Net dry density								NPD	Kg/m ³	
Configuration								1		
Bond strength								NPD	N/mm ²	
Thermal conductivity (⊥10,dry,mat(90,90))								0,49 (S2)	W/mK	
Thermal conductivity (⊥10,dry,mat) EN1745 Annex A								0,45 (S1)	W/mK	
Water vapour permeability□								5/10		
Frost resistance								F2		
Water absorption								17	%	
Initial water absorption								1,5<IW<=4	Kg/(m ² .min)	
Active soluble salts								S2		
Dimensional stability: moisture expansion								NPD	Mm/m	
Reaction to fire								A1		
Dangerous substances								NPD		
Rang sioc								F2 (80°C)		

The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer mentioned above.

Signed for and on behalf of the manufacturer by

Burt Nelissen (General Management)

Lanaken (B)

18.10.2024